

## **DECLARATION of PERFORMANCE**

## NR 03/US5.0/CPR-J-00138-20/2022



- Unique identification code of the product-type: Wood screws Unix type US Ø5.0
  Full thread L = (25 ÷ 60)mm
  Partial thread L=(40 ÷ 70)mm/Lg=(20 ÷ 55)mm; L=80mm/Lg=50mm; L=90,100mm/Lg=55mm;
  L=(120 ÷ 160)mm/Lg=75mm;
  Steel grade C1022 (SAE1022) according to American standard AISI
- 2. Intended use: Screws USø5,0 are intended for fixing of wood
- **3.** Name, registered trade name or registered trade mark and contact address of the manufacturer: Marcopol Sp. z o.o. Producent Śrub, street Oliwska 100, 80-209 Chwaszczyno
- **4.** System or systems of assessment and verification of constancy of performance of the construction product: **System "3" of assessment**
- Declaration of performance concerning by a harmonized standard: EN 14592:2008 + A1:2012 Tab. ZA.1, Name and identification number of the notified body:

## Strojirenský zkušebni ústav, s.p. Brno, Czech Republic, No. 1015

**6.** Declared performance:

Essential characteristic	Performance od product acc. CPR-J-00138-20		Harmonised specification
Characteristic yield moment $M_{\gamma,k}$ [Nmm]	4207		EN 1995-1-1
Characteristic withdrawal parameter f <sub>ax,k</sub> [N/mm2] – for characteristic density of	Perpendicular to the grain	Paraller to the grain	EN 1995-1-1
wood 350 kg/m3	16.31	12.61	
Characteristic head pull- through parameter f <sub>head,k</sub> [N/mm2] – for density of wood 350 kg/m3	24.08		EN 1995-1-1
Characteristic tensile capacity $f_{tens,k}$ [kN]	7.98		EN 1383
Characteristic torsional ratio for density of wood 450 kg/m3	2.57		EN ISO 10666 EN 14592 +A1 annex B
Class of reaction to fire	A1		EN 13501-1
Zinc coating thickness:	min. 2 ÷ 5 μm (service class 1)		EN 1995-1-1



**7.** The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point *6* 

This declaration of performance is issued according to CPR 305/2011 under the sole responsibility of the manufacturer identified in point 3.

Signed by: R&D Director

Chwaszczyno, 21.03.2022

Janusz Kabała

Dyrektor Działu Rozwoju

Produktów Sanusz Kayata