

DECLARATION of PERFORMANCE No 01/HUS5.0-L2/CPR-J-00755-20/2020



- Unique identification code of the product-type: Wood construction screws HUS Ø5.0-L2
 Total length L = (40 ÷ 120) mm; Countershunk head;
 Length L / Length of partial thread L_g 40/24; 50/30; (60÷120)/40

 Steel grade C10B21 according to American Standard AISI
- 2. Intended use: HUS ø5.0-L2 screws are intended for construction fixing of wood
- 3. Name, registered trade name or registered trade mark and contact address of the manufacturer: Marcopol Sp. z o.o. Producer of Bolts str. Oliwska 100, 80-209 Chwaszczyno
- **4.** System or systems of assessment and verification of constancy of performance of the construction product: **System "3" of assessment**
- 5. Declaration of performance concerning by a harmonized standard: EN 14592:2008 + A1:2012 Tab. ZA.1,

Name and identification number of the notified body: **Strojirenský zkušebni ústav, s.p. Brno, Czech Republic, No. 1015**

6. *Declared performance:*

Essential characteristic	Performance od product acc. CPR-J-00755-20		Harmonised specification
Characteristic yield moment M _{y,k} [Nmm]	Thread section	Smooth section	EN 1995-1-1
	14°	14°	
	5987	8789	
	24°	24°	
	6433	9007	
Characteristic withdrawal parameter $f_{ax,k}$ [N/mm²] – for characteristic density of wood 350 kg/m³	Perpendicular to the grain	Parallel to the grain	EN 1995-1-1
	16.33	12.82	
Characteristic head pull- through parameter f _{head,k} [N/mm²] – for density of wood 400 kg/m³	25.58		EN 1995-1-1
Characteristic tensile capacity f _{tens,k} [kN]	8.87		EN 1383
Characteristic torsional ratio for density of wood 350 kg/m ³	2.22		EN ISO 10666 EN 14592 +A1 annex B
Class of reaction to fire	A1		EN 13501-1



Coating thickness	min. 5 μm (Service Class 1 and	EN ISO 4042
Coating thickness	2)	EN 1995-1-1

7. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed by:

Chwaszczyno, 07.05.2020. R&D Director

Janusz Kabała

Dyrektor Działu Rozwoju

Produktów