

## DECLARATION of PERFORMANCE

No 02/CA-Z/H/0284/2021



1. *Unique identification code of the product-type:* **CA-Z/H**
2. *Intended use:* **Torgue controlled expansion wedge anchor CA-H/X are intended to be used for fastening construction structure to concrete**
3. *Name, registered trade name or registered trade mark and contact address of the manufacturer:* **Marcopol Sp. z o.o. Producer of Bolts str. Oliwska 100, 80-209 Chwaszczyno Poland**
4. *System or systems of assessment and verification of constancy of performance of the construction product:* **System "1" of assessment**
5. *European Technical Assessment:* **ETA 19/0284 issued 21.03.2022**  
*Technical Assessment Body:* **Instituto de Ciencias de la Construccion Eduardo Torroja**  
*Notified Body:* **Number: 1219 - Instituto de Ciencias de la Construccion Eduardo Torroja**  
*Certificate of Constancy of Performance:* **1219-CPR-0223**
6. *Declared performance:*

	Essential characteristic	Performance	Technical Specification
<b>3.1 BWR 1: Mechanical resistance and stability</b>			
3.1.1.	Essential characteristic under static or quasi static loading	see table C3 and C5 below	ETA 19/0284
3.1.2.	Displacements under tension and shear loads	see table C7 and C8 below	ETA 19/0284
3.1.3	Essential characteristic under seismic loading categories C1 and C2	see table C9 and C10 below	ETA 19/0284
<b>3.2 BWR 2: Safety in case of fire</b>			
3.2.1.	Reaction to fire	Anchorage satisfy requirements for class A1	EN 13501-1
3.2.2	Resistance to fire	see table C11 below	ETA 19/0284

**Table C3: Essential characteristics under static or quasi-static tension loads according to design method A according to EN 1992-4 for CA-Z/X, CA-H/X, CA-Z/H anchors**

Essential characteristics under static or quasi-static tension loads according to design method A			Performances						
			M8	M10	M12	M16	M20	M24	
<b>Tension loads: steel failure</b>									
$N_{Rk,s}$	Characteristic resistance:	[kN]	18.1	31.4	40.4	72.7	116.6	179.2	
$\gamma_{Ms}$	Partial safety factor:	[-]	1.5	1.5	1.5	1.5	1.5	1.5	
<b>Tension loads: pull-out failure in concrete</b>									
<b>CA-Z/X anchor</b>									
$N_{Rk,p,ucr}$	Characteristic resistance in C20/25 uncracked concrete:	[kN]	9	16	20	35	50	50	
$N_{Rk,p,cr}$	Characteristic resistance in C20/25 cracked concrete:	[kN]	5	9	12	25	30	30	
<b>CA-H/X anchor</b>									
$N_{Rk,p,ucr}$	Characteristic resistance in C20/25 uncracked concrete:	[kN]	9	16	30	35	50	--	
$N_{Rk,p,cr}$	Characteristic resistance in C20/25 cracked concrete:	[kN]	6	9	16	25	30	--	
<b>CA-Z/H anchor</b>									
$N_{Rk,p,ucr}$	Characteristic resistance in C20/25 uncracked concrete:	[kN]	9	16	25	35	50	--	
$N_{Rk,p,cr}$	Characteristic resistance in C20/25 cracked concrete:	[kN]	6	9	16	25	30	--	
$\gamma_{ins}$	Installation safety factor:	[-]	1.2	1.0	1.0	1.0	1.0	1.2	
$\Psi_c$	Increasing factor for $N^0_{Rk,p}$ :	C30/37	[-]	1.22	1.16	1.22	1.22	1.16	1.22
		C40/50	[-]	1.41	1.31	1.41	1.41	1.31	1.41
		C50/60	[-]	1.55	1.41	1.55	1.55	1.41	1.55
<b>Tension loads: concrete cone and splitting failure</b>									
$h_{ef}$	Effective embedment depth:	[mm]	48	60	70	85	100	125	
$k_{ucr,N}$	Factor for uncracked concrete:	[-]	11.0						
$k_{cr,N}$	Factor for cracked concrete:	[-]	7.7						
$\gamma_{ins}$	Installation safety factor:	[-]	1.2	1.0	1.0	1.0	1.0	1.2	
$S_{cr,N}$	Concrete cone failure:	[mm]	3 x $h_{ef}$						
$C_{cr,N}$		[mm]	1.5 x $h_{ef}$						
$S_{cr,sp}$	Splitting failure:	[mm]	288	300	350	425/510 <sup>1)</sup>	500/600 <sup>1)</sup>	560	
$C_{cr,sp}$		[mm]	144	150	175	213/255 <sup>1)</sup>	250/300 <sup>1)</sup>	280	

<sup>1)</sup> Respective values for anchors CA-Z/X / CA-H/X, CA-Z/H

**Table C5: Essential characteristics under static or quasi-static shear loads of design method A according to EN 1992-4 for CA-Z/X, CA-H/X, CA-Z/H anchors**

Essential characteristics under static or quasi-static shear loads according to design method A			Performances					
			M8	M10	M12	M16	M20	M24
<b>Shear loads: steel failure without lever arm</b>								
$V_{Rk,s}$	Characteristic resistance:	[kN]	11.0	17.4	25.3	47.1	73.1	84.7
$k_7$	Ductility factor:	[-]	1.00					
$\gamma_{Ms}$	Partial safety factor:	[-]	1.25	1.25	1.25	1.25	1.25	1.25
<b>Shear loads: steel failure with lever arm</b>								
$M^0_{Rk,s}$	Characteristic bending moment:	[Nm]	22.5	44.8	78.6	199.8	389.4	673.5
$\gamma_{Ms}$	Partial safety factor:	[-]	1.25	1.25	1.25	1.25	1.25	1.25
<b>Shear loads: concrete pryout failure</b>								
$k_8$	Pryout factor:	[-]	1	2	2	2	2	2
$\gamma_{ins}$	Installation safety factor:	[-]	1.00					
<b>Shear loads: concrete edge failure</b>								
$l_f$	Effective length of anchor under shear loads:	[mm]	48	60	70	85	100	125
$d_{nom}$	Outside anchor diameter:	[mm]	8	10	12	16	20	24
$\gamma_{ins}$	Installation safety factor:	[-]	1.00					

**Table C7: Displacements under tension loads for CA-Z/X, CA-H/X, CA-Z/H, CA-X/X anchors**

Displacements under tension loads			Performances					
			M8	M10	M12	M16	M20	M24
<b>CA-Z/X anchor</b>								
N	Service tension load:	[kN]	2.5	4.3	6.3	10.4	13.9	18.0
$\delta_{N0}$	Short term displacement:	[mm]	1.1	0.7	1.0	0.4	1.6	0.4
$\delta_{N\infty}$	Long term displacement:	[mm]	1.9	1.9	1.9	1.9	1.9	2.0
<b>CA-H/X anchor</b>								
N	Service tension load:	[kN]	2.5	4.3	6.3	10.4	13.9	--
$\delta_{N0}$	Short term displacement:	[mm]	1.0	1.1	0.9	1.5	1.2	--
$\delta_{N\infty}$	Long term displacement:	[mm]	1.9	1.9	1.9	1.9	1.9	--
<b>CA-Z/H anchor</b>								
N	Service tension load:	[kN]	2.5	4.3	7.6	11.9	14.3	--
$\delta_{N0}$	Short term displacement:	[mm]	1.0	1.1	0.9	1.5	1.3	--
$\delta_{N\infty}$	Long term displacement:	[mm]	1.6	1.6	1.6	1.6	1.6	--
<b>CA-X/X anchor</b>								
N	Service tension load in non cracked concrete:	[kN]	5.7	7.6	8.7	15.3	19.5	--
$\delta_{N0}$	Short term displacement:	[mm]	1.4	1.4	1.4	1.8	1.8	--
$\delta_{N\infty}$	Long term displacement:	[mm]	1.9	1.9	1.9	1.9	1.9	--
<b>CA-X/X anchor</b>								
N	Service tension load in cracked concrete:	[kN]	4.0	6.7	7.5	10.7	13.7	--
$\delta_{N0}$	Short term displacement:	[mm]	1.2	1.3	1.3	1.3	1.3	--
$\delta_{N\infty}$	Long term displacement:	[mm]	1.7	1.7	1.7	1.7	1.7	--

**Table C8: Displacements under shear load for CA-Z/X, CA-H/X, CA-Z/H, CA-X/X anchors**

Displacements under shear loads		Performances						
		M8	M10	M12	M16	M20	M24	
<b>CA-Z/X anchor</b>								
V	Service shear load:	[kN]	4.9	6.8	8.5	15.1	24.6	33.6
$\delta_{V0}$	Short term displacement:	[mm]	1.0	1.5	1.8	1.9	3.1	1.4
$\delta_{V\infty}$	Long term displacement:	[mm]	1.5	2.3	2.7	2.9	4.7	2.1
<b>CA-H/X anchor</b>								
V	Service shear load:	[kN]	4.9	6.8	8.5	15.1	24.6	-
$\delta_{V0}$	Short term displacement:	[mm]	1.0	1.5	1.8	1.9	3.1	--
$\delta_{V\infty}$	Long term displacement:	[mm]	1.5	2.3	2.7	2.9	4.7	--
<b>CA-Z/H anchor</b>								
V	Service shear load:	[kN]	4.9	6.8	8.5	15.1	24.6	--
$\delta_{V0}$	Short term displacement:	[mm]	1.0	1.5	1.8	1.9	3.1	--
$\delta_{V\infty}$	Long term displacement:	[mm]	1.5	2.3	2.7	2.9	4.7	--
<b>CA-X/X anchor</b>								
V	Service shear load:	[kN]	6.8	10.8	15.7	31.4	46.9	--
$\delta_{V0}$	Short term displacement:	[mm]	1.9	1.6	1.6	2.2	2.2	--
$\delta_{V\infty}$	Long term displacement:	[mm]	2.4	2.4	2.4	3.3	3.3	--

**Table C9: Essential characteristics for seismic performance category C1 CA-Z/X, CA-Z/H anchors**

Essential characteristics for seismic performance category C1		Performances						
		M8	M10	M12	M16	M20	M24	
<b>Steel failure for tension and shear failure</b>								
$N_{Rk,s,C1}$	Characteristic tension steel failure:	[kN]	18.1	31.4	40.4	72.7	116.6	--
$\gamma_{Ms,N}$	Partial safety factor:	[-]	1.5	1.5	1.5	1.5	1.5	--
$V_{Rk,s,C1}$	Characteristic shear steel failure:	[kN]	7.7	12.2	17.8	33.0	58.5	--
$\gamma_{Ms,V}$	Partial safety factor:	[-]	1.25	1.25	1.25	1.25	1.25	--
<b>Pull out failure</b>								
<b>CA-Z/X anchor</b>								
$N_{Rk,p,C1}$	Characteristic pull out failure:	[kN]	--	5.3	8.4	17.5	--	--
<b>CA-Z/H anchor</b>								
$N_{Rk,p,C1}$	Characteristic pull out failure:	[kN]	5.9	8.9	16.0	25.0	30.0	--
$\gamma_{fins}$	Installation safety factor:	[-]	1.2	1.0	1.0	1.0	1.0	--
<b>Concrete cone failure</b>								
$h_{ef}$	Effective embedment depth:	[mm]	48	60	70	85	100	--
$s_{cr,N}$	Spacing:	[mm]	3 x $h_{ef}$					--
$c_{cr,N}$	Edge distance:	[mm]	1.5 x $h_{ef}$					--
$\gamma_{fins}$	Installation safety factor:	[-]	1.2	1.0	1.0	1.0	1.0	--
<b>Concrete pryout failure</b>								
$k_8$	Pryout factor:	[-]	1	2	2	2	2	--
<b>Concrete edge failure</b>								
$l_f$	Effective length of anchor:	[mm]	48	60	70	85	100	--
$d_{nom}$	Outside anchor diameter:	[-]	8	10	12	16	20	--

**Table C10: Essential characteristics for seismic performance category C2 CA-Z/X, CA-Z/H anchors**

Essential characteristics for seismic performance category C2			Performances					
			M8	M10	M12	M16	M20	M24
<b>Steel failure for tension and shear failure</b>								
$N_{RK,s,C2}$	Characteristic tension steel failure:	[kN]	--	31.4	40.4	72.7	116.6	--
$\gamma_{Ms,N}$	Partial safety factor:	[-]	--	1.5	1.5	1.5	1.5	--
$V_{RK,s,C2}$	Characteristic shear steel failure:	[kN]	--	12.2	17.8	33.0	58.5	--
$\gamma_{Ms,V}$	Partial safety factor:	[-]	--	1.25	1.25	1.25	1.25	--
<b>Pull out failure</b>								
<b>CA-Z/X anchor</b>								
$N_{RK,p,C2}$	Characteristic pull out failure:	[kN]	--	--	5.2	8.9	--	--
<b>CA-Z/H anchor</b>								
$N_{RK,p,C2}$	Characteristic pull out failure:	[kN]	--	3.9	9.1	--	21.0	--
$\gamma_{ins}$	Installation safety factor:	[-]	--	1.0	1.0	1.0	1.0	--
<b>Concrete cone failure</b>								
$h_{ef}$	Effective embedment depth:	[mm]	--	60	70	85	100	--
$s_{cr,N}$	Spacing:	[mm]	--	3 x $h_{ef}$				--
$c_{or,N}$	Edge distance:	[mm]	--	1.5 x $h_{ef}$				--
$\gamma_{ins}$	Installation safety factor:	[-]	--	1.0	1.0	1.0	1.0	--
<b>Concrete pryout failure</b>								
$k_8$	Pryout factor:	[-]	--	2	2	2	2	--
<b>Concrete edge failure</b>								
$l_f$	Effective length of anchor:	[mm]	--	60	70	85	100	--
$d_{nom}$	Outside anchor diameter:	[-]	--	10	12	16	20	--
<b>Displacements</b>								
<b>CA-Z/X anchor</b>								
$\bar{\delta}_{N,C2} (DLS)$	Displacement Damage Limitation State: <sup>1) 2)</sup>	[mm]	--	--	2.34	3.99	--	--
$\bar{\delta}_{V,C2} (DLS)$	Displacement Damage Limitation State: <sup>1) 2)</sup>	[mm]	--	--	5.53	5.96	--	--
$\bar{\delta}_{N,C2} (ULS)$	Displacement Ultimate Limit State: <sup>1)</sup>	[mm]	--	--	9.54	10.17	--	--
$\bar{\delta}_{V,C2} (ULS)$	Displacement Ultimate Limit State: <sup>1)</sup>	[mm]	--	--	9.08	10.66	--	--
<b>CA-Z/H anchor</b>								
$\bar{\delta}_{N,C2} (DLS)$	Displacement Damage Limitation State: <sup>1) 2)</sup>	[mm]	--	3.15	5.57	--	6.82	--
$\bar{\delta}_{V,C2} (DLS)$	Displacement Damage Limitation State: <sup>1) 2)</sup>	[mm]	--	5.61	5.53	--	6.37	--
$\bar{\delta}_{N,C2} (ULS)$	Displacement Ultimate Limit State: <sup>1)</sup>	[mm]	--	14.77	20.31	--	29.12	--
$\bar{\delta}_{V,C2} (ULS)$	Displacement Ultimate Limit State: <sup>1)</sup>	[mm]	--	8.68	9.08	--	12.32	--

<sup>1)</sup> The listed displacements represent mean values

<sup>2)</sup> A small displacement may be required in the design in the case of displacements sensitive fastening of "rigid" supports. The characteristics resistance associated with such small displacements may be determined by linear interpolation or proportional reduction.

**Table C11: Essential characteristics under fire exposure CA-Z/X, CA-H/X, CA-Z/H anchors**

Essential characteristics under fire exposure				Performances					
				M8	M10	M12	M16	M20	M24
<b>Steel failure</b>									
$N_{Rk,s,fl}$	Characteristic tension resistance:	R30	[kN]	0,4	0,9	1,7	3,1	4,9	7,1
		R60	[kN]	0,3	0,8	1,3	2,4	3,7	5,3
		R90	[kN]	0,3	0,6	1,1	2,0	3,2	4,6
		R120	[kN]	0,2	0,5	0,8	1,6	2,5	3,5
$V_{Rk,s,fl}$	Characteristic shear resistance:	R30	[kN]	0,4	0,9	1,7	3,1	4,9	7,1
		R60	[kN]	0,3	0,8	1,3	2,4	3,7	5,3
		R90	[kN]	0,3	0,6	1,1	2,0	3,2	4,5
		R120	[kN]	0,2	0,5	0,8	1,6	2,5	3,5
$M^0_{Rk,s,fl}$	Characteristic bending resistance:	R30	[Nm]	0,4	1,1	2,6	6,7	13,0	22,5
		R60	[Nm]	0,3	1,0	2,0	5,0	9,7	16,8
		R90	[Nm]	0,3	0,7	1,7	4,3	8,4	14,6
		R120	[Nm]	0,2	0,6	1,3	3,3	6,5	11,2
<b>Pull out failure</b>									
$N_{Rk,p,fl}$	Characteristic resistance:	R30	[kN]	1,3/1,5 <sup>3)</sup>	2,3	3,0/4,0 <sup>3)</sup>	6,3	7,5	7,5
		R60	[kN]	1,0/1,2 <sup>3)</sup>	1,8	2,4/3,2 <sup>3)</sup>	5,0	6,0	6,0
		R90	[kN]						
		R120	[kN]						
<b>Concrete cone failure <sup>2)</sup></b>									
$N_{Rk,c,fl}$	Characteristic resistance:	R30	[kN]	2,9	5,0	7,4	12,0	18,0	31,4
		R60	[kN]						
		R90	[kN]						
		R120	[kN]	2,3	4,0	5,9	9,6	14,4	25,2
$S_{cr,N,fl}$	Critical spacing:	R30 to R120	[mm]	4 x $h_{ef}$					
$S_{min,fl}$	Minimum spacing:	R30 to R120	[mm]	50	60	70	85/128 <sup>1)</sup>	100/150 <sup>1)</sup>	125
$C_{cr,N,fl}$	Critical edge distance:	R30 to R120	[mm]	2 x $h_{ef}$					
$C_{min,fl}$	Minimum edge distance:	R30 to R120	[mm]	$C_{min} = 2 \times h_{ef}$ ; if fire attack comes from more than one side, the edge distance of the anchor has to be $\geq 300$ mm and $\geq 2 \times h_{ef}$					
<b>Concrete pry out failure</b>									
$k_{s,fl}$	Pryout factor:	R30 to R120	[-]	1	2	2	2	2	2

<sup>1)</sup> Respective values for anchors CA-Z/X / CA-H/X, CA-Z/H

<sup>2)</sup> As a rule, splitting failure can be neglected since cracked concrete and reinforcement is assumed.

In absence of other national regulations the partial safety factor for resistance under fire exposure  $\gamma_{m,fl} = 1,0$  is recommended

**7. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6**

**This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.**

Chwaszczyno, 12.04.2022

Signed by:

R&D Director

Janusz Kabała

Dyrektor Działu Rozwoju  
Produktów



Janusz Kabała