

## **DECLARATION of PERFORMANCE**

## NR 02/GW7.0/E-30-20372-17/2017



**1.** Unique identification code of the product-type:

## **Construction nails type GW**

Steel SAE1008 according to ASTM A510M – minimum tensile strength R<sub>m</sub> ≥ 450 N/mm<sup>2</sup>

- nominal diameter d = 7,0 mm
- lenght I =(200 ÷ 250) mm
- head area  $A_h = 153,86 (+/-15) \text{ mm}^2$
- **2.** *Intended use:*

GW Ø7,0 construction nails are intended for structural connections of load-bearing wooden elements.

**3.** Name, registered trade name or registered trade mark and contact address of the manufacturer:

Marcopol Sp. z o.o. Producent Śrub, street Oliwska 100, 80-209 Chwaszczyno

- **4.** System or systems of assessment and verification of constancy of performance of the construction product: **System "3" of assessment**
- **5.** Declaration of performance concerning by a harmonized standard:

EN 14592:2008 + A1:2012 Tab. ZA.1,

Name and identification number of the notified body:

Strojirenský zkušebni ústav, s.p. Brno, Czech Republic, No. 1015

**6.** *Declared performance:* 

Essential characteristic	Performance od product acc. E-30-20372-17		Harmonised specification
Characteristic yield moment M <sub>y,k</sub> [Nmm]	51 484		EN 1995-1-1
Characteristic withdrawal parameter f <sub>ax,k</sub> [N/mm2] – for characteristic density of wood 350 kg/m3	Perpendicular to the grain	Paraller to the grain	- EN 1995-1-1
	3,09	2,03	
Characteristic head pull- through parameter fhead,k [N/mm2] – for density of wood 350 kg/m3	21,45		EN 1995-1-1
Characteristic tensile capacity f <sub>tens,k</sub> [kN]	25,94		EN 1383
Class of reaction to fire	A1		EN 13501-1
Zinc coating thickness:	min. 5 μm (service class 1)		EN 1995-1-1



7. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point *6*.

This declaration of performance is issued according to CPR 305/2011 under the sole responsibility of the manufacturer identified in point 4.

Signed by:

Chwaszczyno, 15.09.2017

**R&D Director** 

Janusz Kabała

Dyrektor Działu Rozwoju

Produktów