

## **DECLARATION of PERFORMANCE**

## NR 02/US3.5.INOX/E-30-20359-14/2017



1. Unique identification code of the product-type: Wood screws US ø3.5

Full thread  $L = (25 \div 45)$ mm

Partial thread L= $(40 \div 70)$ mm; L<sub>g</sub>= $(18 \div 35)$  mm;

Stainless steel grade 304 according to American standard AISI

- 2. Intended use: Screws USø3,5 are intended for fixing of wood
- 3. Name, registered trade name or registered trade mark and contact address of the manufacturer: Marcopol Sp. z o.o. Producent Śrub, street Oliwska 100, 80-209 Chwaszczyno
- **4.** System or systems of assessment and verification of constancy of performance of the construction product: **System "3" of assessment**
- 5. Declaration of performance concerning by a harmonized standard: EN 14592:2008 + A1:2012 Tab. ZA.1,

Name and identification number of the notified body: **Strojirenský zkušebni ústav, s.p. Brno, Czech Republic, No. 1015** 

**6.** Declared performance:

Essential characteristic	Performance od product acc. E-30-20359-14		Harmonised specification
Characteristic yield moment M <sub>y,k</sub> [Nmm]	1 688		EN 1995-1-1
Characteristic withdrawal parameter f <sub>ax,k</sub> [N/mm2] – for characteristic density of wood 440 kg/m3	Perpendicular to the grain	Paraller to the grain	EN 1995-1-1
WOOD 440 Kg/ III3	20.22	12.35	
Characteristic head pull- through parameter f <sub>head,k</sub> [N/mm2] – for density of wood 440 kg/m3	23.01		EN 1995-1-1
Characteristic tensile capacity f <sub>tens,k</sub> [kN]	2.27		EN 1383



Characteristic torsional ratio for density of wood 450 kg/m3	1.52	EN ISO 10666 EN 14592 +A1 annex B
Class of reaction to fire	A1	EN 13501-1
Corrosion Resistance:	Stainless steel AISI 304 service class 3	EN 1995-1-1

7. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6

This declaration of performance is issued according to CPR 305/2011 under the sole responsibility of the manufacturer identified in point 3.

Signed by:

Chwaszczyno, 26.09.2017.

**R&D** Director

Janusz Kabała

Dyrektor Działu Rozwoju Produktów

rbala 10